

## USES

It is pre-mixed, quality assured mortar comprising of Ordinary Portland Cement, specially graded sand and Polymers. It is specially formulated and easily applied, giving a better bonding with higher air entraining properties.

## Area Of Application

- ✓ To join fly ash bricks, cement block, hollow blocks, aerated block etc.
- ✓ Jointing of prestressed concrete slabs, panels.
- ✓ Jointing of cement window and door frames.
- ✓ Barbecues and fire places.
- ✓ Garden and boundary walls.

## Properties

- ✓ quick setting proprietary mortar essentially “glues” the block together and the next course is ready to lay within a very short time.
- ✓ Higher bonding strength increases durability and eliminates future maintenance.
- ✓ Non-metallic doesn't rust out, will not discolor wall.
- ✓ Ready mixed mineral based products designed for new construction as well as for renovation purpose.
- ✓ Being premixed, it saves considerable time, labour and increases dimensional stability of the blocks.
- ✓ Being premixed and less porous, it inhibits efflorescence.

## Technical Details

- |                  |  |
|------------------|--|
| ✓ Color:         | Grey                                   |
| ✓ Storage:       | Store in dry place                     |
| ✓ Shelf life:    | 6 months                               |
| ✓ Hard dry:      | Approx. 45 minutes                     |
| ✓ Bed Thickness: | 3-4 mm                                 |
| ✓ Coverage:      | Approx 200sq ft/40kg @3-4 mm thickness |
| ✓ Packing size:  | 5 kg and 25 kg                         |