

USES

It is a high strength and flexible single component and ready to use product, only water is to be added. It is used for fixation of multiple substrates such as stones, wood, glass or metal and it can be applied on both walls and floors.

PROPERTIES

- ✓ Shock and water resistant
- ✓ Can be used to join variable differed substrate such as Wood, Metal, Glass, Stones and Glass Tiles to concrete masonry.
- ✓ Reduce Application time to 1/3 of conventional system.
- ✓ Very easy to apply that one can apply himself
- ✓ High flexibility and strength which allows fixing of large dimension Stone.
- ✓ Very good anti-slip properties
- ✓ Can be used for both Wall & Floors
- ✓ Long open time and very high shear bond strength
- ✓ It has anti-sagging properties i.e no need of distance splinters
- ✓ Thickness: 1.5-5 mm.
- ✓ It is non-shrinkable and waterproof
- ✓ Suitable for thick and thin bed application (3mm- 12mm)
- ✓ One must use the newly laid floor after 24hrs since it has been laid

Area Of Application

- ✓ Used for commercial purposes
- ✓ Used for residential purposes
- ✓ Used for both interior and exterior applications
- ✓ Fabulous for underwater applications
- ✓ Excellent for facades
- ✓ It is used for all ceramic tile, vitrified tile, stone, wooden frame, glass tiles, metal frame installations
- ✓ Vertical cladding

Suitable Substrate

- ✓ For concrete masonry
- ✓ For cement mortar beds & cement terrazzo
- ✓ Concrete block
- ✓ Plastic laminate
- ✓ Gypsum wallboard & gypsum plaster
- ✓ Large Ceramic tile.
- ✓ Cement plaster
- ✓ Brick masonry
- ✓ Wood Frames
- ✓ Natural and Artificial Stone
- ✓ Glass and Glass Tiles.

Technical Details

- ✓ Color: White, Grey
- ✓ Mesh size: Below 30 mesh
- ✓ Bulk density: Approx. 1400-1500 kg/cubic meter
- ✓ Drying time hours: 24 hrs
- ✓ Coverage/kg: 4 sqft for 3mm thick layer
- ✓ Open time: Approx. 2 hrs. At 30 degree centigrade
- ✓ Trafficable time: 24 hrs (max)
- ✓ Shelf life: 12 months in dry condition
- ✓ Packing size: 5 kg and 25 kg

