

### Composition

Mixture of specialty polymer

### Uses

Permanent, solvent-borne anti-graffiti-coating, 1-component

### Properties

- ✓ Decreased adhesion of aerosol paints
- ✓ Easy removal of aerosol paints (graffiti)
- ✓ Highly water-repellent & weather-resistant
- ✓ Forms a visible, transparent Coat
- ✓ 1-component, reacts with moisture to polymerize
- ✓ Suitable for mineral backgrounds, wood and metal.
- ✓ solvent borne
- ✓ Markers, stickers, chewing gums etc, achieve only poor adhesion on the coating and can be removed easily.
- ✓ The coating is transparent and leads to a deepening of the substrate's color with a slight gloss.

### Application

1. Clean the surface makes and sure it's free from any foreign particles and moisture.
2. Use hand gloves to handle material.
3. Apply 2-3 coats in interval of 1 hr with paint brush, airless spray or roller.
4. Make sure area is well ventilated and dust do not settle while application coat.
5. Give curing time of 36 Hr.
6. Open Pot Life of material is 2 Hr.

### Storage

- If stored below 0 °C, the product may solidify and/ or change its consistency, after heating to 20° - 25°C and thorough mixing; the product can be used again without any problems.
- The content of the drums must not be exposed to moisture or be left open for a long time. Irreparable damage is possible. Close the drums tightly after use.

### Attention

The above recommendations are based on comprehensive studies and practical experience. They are, however, without liability regarding property rights of third parties and foreign laws. The user should test for himself whether the product and the application are suited for his very special purposes. We are, above all, not liable for fields and methods of application which have not been put down by us in writing. Advice for making regulations and protective measures can be taken from the respective safety data sheet.