



Cell: +91-9375034083

Stone Sealer -11

- ✓ Protects against stains
- ✓ Preserves stones natural Beauty.
- ✓ Oil and grease-repellent
- ✓ Easy-to-use
- ✓ Great for natural stone countertops
- ✓ Gives Color Enhancing Effect to Natural Stone.

Where To Use

For all absorbent natural or artificial stones, such as marble, travertine, Solnhofen slabs, sand-stone, concrete blocks, terrazzo, granite, cotta coverings

Direction To Use

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Be sure surface is clean and free of waxes and coatings. Sealer may be applied to damp surfaces 1 hour after standing water is removed. Surface temperature should be between 50°F and 80°F. Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets off of treated surface until it is dry.

- 1. Mask off and protect any surfaces not intended to be t reated.
- 2. Liberally apply an even coat on surfaces being treated.
- 3. Allow sealer to penetrate surface for 15–20 minutes while spreading sealer over entire area to ensure even penetration. Remove excess sealer by wiping surface thoroughly with clean, dry towels.
- 4. Apply second coat as needed for porous, absorbent surfaces. Apply 15–20 minutes after first coating as directed in steps 2-3.
- 5. 20 minutes after final application, wipe entire surface with clean, dry towels to remove any excess sealer. To remove any residue, reapply a thin coat of sealer, wait 2–3 minutes, and then rub lightly with a white nylon pad. Wipe again thoroughly with clean, dry towels.
- $6. \ A \ full \ cure \ is \ achieved \ after \ 24-72 \ hours.$ Foot traffic may begin in 6-8 hours.











Cell: +91-9375034083

Typical Coverage

Expected 100-125SqFeetWearfor two Coats Depending on the porosity of the surface. 3–5 years on interior surfaces and 1–3 years on exterior surfaces. For frequently used surfaces, annual sealing is recommended.

ATTENTION

The above recommendations are based on comprehensive studies and practical experience. They are, however, without liability regarding property rights of third parties and foreign laws. The user should test for himself whether the product and the application are suited for his very special purposes. We are, above all, not liable for fields and methods of application which have not been put down by us in writing.



Treated with Stone Sealer-11

Untreated





