

Wood Coat

Wood Coat is a multifunctional, nearly VOC-free, water-borne silane system.

Scope Of Application

- Wood impregnated with the new silicone resin emulsion **Wood-Coat** is protected against damp, moisture and damage caused by fungi and insects for an exceedingly long time.
- It possesses hydrophobic properties that reliably protect wood outdoors against wet and damp and the damage that these cause.
- Weathering tests show that the product still protects impregnated wood against moisture and damp. This means that silicone resins, which have proved successful at protecting mineral substrates over the decades, can now provide wood with lasting outdoor protection, too.
- The wood is better protected against typical damage, such as fungus, mildew and insect attack, as well as cracks caused by swelling and shrinking. Recommended dosage during application: For a full range effectiveness and durability (up to 1500 h of QUV-stability in transparent systems) 300 g/m² of undiluted Wood Coat are necessary. That amount can be applied by either one-step or multi-step procedures, depending on the absorptiveness of the wood substrate.
- Easy for application.

Area Of Application

- ✓ Pool Side Wood Flooring
- ✓ Home Furniture & Decor
- ✓ Bath Room Wooden Floor
- ✓ Tree House
- ✓ Garden Furniture
- ✓ Open wooden flooring

Curing Time: 1 -2 weeks

Packing Size: 20 Ltrs