

Stone Sealer LIT

Stone Sealer LIT is a Solvent Based Water & Oil Repellent System for Polished Surfaces.

Technical Specification

Formulated with organic resin dispersed in hydrocarbon solvent.

Advantages

- Protects against water and oil base stains.
- Preserves stone's natural beauty.
- Does not form any surface film.
- Suitable for interior and exterior application and counter tops.
- No Color Change in Dark Stone
- Breathable by nature.
- U V resistance.
- Great for natural stone countertops.
- Low VOC
- Easy-to-use.

Where to Use

- ✓ Marble
- ✓ Granite
- ✓ Sand Stone
- ✓ Concrete

Technical Data

- Appearance: clear, liquid
- Odor less
- Specific gravity at 20°C: ca. 0.78 g/cm³
- Application Temperature 15-30 °C
- Drying time 4 Hr.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- **Apply Sealer:** Spread evenly for full coverage.
- **Penetration Time:** Allow 25–30 minutes to soak in.
- **Re-apply if Needed:** Repeat for porous surfaces.
- **Remove Excess:** Wipe off with clean, dry towels.
- **Curing:** Let it cure for 24-48 hours before use.

Typical Coverage

- Marble 10- 30* Sq Mt Per Ltr
- Granite 10- 30* Sq Mt Per Ltr
- Sand Stone 4- 10* Sq Mt Per Ltr
- Concrete 4- 10* Sq Mt Per Ltr

Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Application Method

Brush: Paint Brush with Soft bristle.

Fabric Roller: Short bristle.

Cotton Cloth: Clean White Cotton Cloth.

Garden Spray: Low Pressure High Volume.



Standard Testing Method

- **Water Repellency:** ASTM C67 or ASTM C140
- **Stain Resistance:** ASTM D1308
- **Breathability:** ASTM E96
- **UV Resistance:** ASTM G154
- **Accelerated Weathering:** ASTM G155

Pack Size

- 1 LTR
- 5 LTR
- 20 LTR
- 30 LTR
- 50 LTR

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use
- Flammable.



Trinity Rubber

70963 34083

"J" Type Shed , Plot No. 2314,Phase -
III, G.I.D.C. Area,Vapi 396195

info@waterrepellent.in