Floor Ptect 15

Floor Ptect 15 is A Solvent Free System to Provide Dark Look to Polished and Unpolished Surfaces.

Technical Specification

Organic Resin dispersed in Oil.

Advantages

- Wet look that enriches the natural color and texture.
- Highlights the stone's natural beauty, making patterns and textures more pronounced
- Protects the stone from stains caused by oils, grease, and water.
- U V resistance.
- Forms Invisible thin film.
- Best for vertical and horizontal application.
- VOC and Solvent Free
- Easy-to-use.

Where to Use

- ✓ Marble
- ✓ Granite
- ✓ Sand Stone
- ✓ Concrete

Technical Data

- Appearance: clear, liquid
- Odor less
- Specific gravity at 20°C: ca. 1.02 g/cm³
- Application Temperature 15-30 °C
- Drying time 4 Hr.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- **Apply Sealer:** Spread one coat evenly till the surface is drenched for full coverage. Remove excess material after 10 mins of application.
- **After 24 hours:** Apply second coat only if required.
- **Remove Excess:** Wipe off with clean, dry towels.
- **Curing:** Let it cure for 24-48 hours before use.

Typical Coverage

- Marble 10- 40* Sq Mt Per Ltr
- Granite 10- 40* Sq Mt Per Ltr
- Sand Stone 5- 20* Sq Mt Per Ltr.
- Concrete 5- 10* Sq Mt Per Ltr.

Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Application Method

Brush: Paint Brush with Soft Bristle.
Fabric Roller: Short Bristle.
Cotton Cloth: Clean White Cotton Cloth.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in

Standard Testing Method

- Water Repellency: ASTM C67 or ASTM C140
- Stain Resistance: ASTM D1308
- Breathability: ASTM E96
- UV Resistance: ASTM G154
- Accelerated Weathering: ASTM G155

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Flammable.

Pack Size

- 1 KG
- 5 KG
- 20 KG
- 30 KG
- 50 KG

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in