Glass Coat 100

Glass Coat 100 is Solvent Based System for Glass, Solar Panel and Mirrors

Technical Specification

Organic resin dispersed with hydrocarbon

Advantages

- Crystal Clear Invisible Protection
- Maintains Original Transparency and Light Transmission
- Easy-Clean Technology Reduces Dirt and Dust Build-Up
- Water Repellent Surface for Improved Visibility
- Helps Minimize Water Marks and Staining
- UV Resistant for Long-Term Outdoor Performance
- Enhances Durability of Glass and Mirror Surfaces
- Non-Yellowing Transparent Coating
- Fast and Simple Application Process
- Best for vertical application.
- VOC Free
- Easy-to-use.

Where to Use

- ✓ Glass
- ✓ Mirror

Technical Data

- Appearance: Yellow to clear, liquid
- Sweet Odor.
- Specific gravity at 20°C: ca. 0.70 g/cm³
- Application Temperature 15-30 °C
- Drying time 4 Hr.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- Clean Glass or Mirror Surface with alcohol based cleaner.
- **Apply Sealer:** Spread two coats evenly till the surface is drenched for full coverage.
- **Penetration Time**: Allow 2 Hrs. to soak in.
- **Remove Excess:** Wipe off with clean, dry soft tissue paper.
- **Curing:** Let it cure for 24-48 hours before use.

Typical Coverage

- Glass Or Mirror 80- 100* Sq Mt Per Ltr

Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in

Application Method

Cotton Cloth: Clean With White Cotton Cloth.
Garden Spray: Low Pressure High Volume.

Standard Testing Method

- Water Repellency: ASTM C67 or ASTM C140

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Flammable.

Pack Size

- 1 LTR
- 5 LTR
- 20 LTR
- 30 LTR
- 50 LTR

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in