Klynn Cemnt

Klynn Cemnt is used to remove cement film, mortar and grout haze

Technical Specification

Formulated with specialty chemicals.

Advantages

- Removes cement film and grout haze
- Easy to use.

Where to Use

- ✓ Marble
- ✓ Granite
- ✓ Ceramic
- ✓ Concrete
- ✓ Natural and Artificial stone

Technical Data

- Appearance Red, liquid
- Mild Pungent smell
- Specific gravity at 20°C: ca. 1.20 g/cm³
- Application Temperature 15-30 °C
- Drying time 20 Mins.

Directions for Use

- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

1. Use rubber gloves for cleaner application.
2. Shake well before use.
3. Dilute in 1:1 ratio with potable water.
4. Apply the product using a scrubber, brush, or cleaning pad.
5. Allow cleaner to act on surface for 15 to 20 minutes.
6. Rub gently with a metal scrubber, brush or cleaning pad.
7. Wash surface with clean water and wipe with dry and clean cloth.
8. Repeat the process if necessary.
9. For harsh stain use 100% material.

Typical Coverage

- Depending on the type of stain.

Application Method

Brush: Paint Brush with Soft Bristle.
Cotton Cloth: Clean White Cotton Cloth.
Garden Spray: Low Pressure High Volume.
Dipping: Material can be submerged in a pond of chemical.

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Highly acidic can cause skin burns on contact.
- Wash hands thoroughly after handling.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in

- Don’t use on marble and lime stone.

Pack Size

- 1 LTR
- 5 LTR
- 20 LTR
- 30 LTR

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in