Leather Coat 146

Leather coat 146 is Breathable Water & Oil Repellent in Solvent Based System for Fabric and Leather.

Technical Specification

Formulated with Organic Resin dispersed in Hydrocarbon.

Advantages

- Protects against water and oil stains.
- Maintains Natural Look and Feel of Leather
- Preserves Fabric Softness and Flexibility
- Does not form any surface film.
- Breathable by nature.
- U V resistance.
- Best for all leather.
- Low VOC.
- Easy-to-use.

Where to Use

- ✓ Cotton.
- ✓ Silk.
- ✓ Polyester
- ✓ Denim
- ✓ Leather

Technical Data

- Appearance: Yellow to clear, liquid
- Odor less
- Specific gravity at 20°C: ca. 0.78 g/cm³
- Application Temperature 15-30 °C
- Drying time 4 Hr.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- **Apply Sealer:** Spread two coats evenly till the surface is drenched for full coverage.
- **Penetration Time**: Allow 25–30 minutes to soak in.
- **Remove Excess:** Wipe off with clean, dry towels.
- **Curing:** Let it cure for 24-48 hours before use.

Typical Coverage

- Cotton 3 - 5 * Sq Mt Per Ltr
- Silk 3- 5* Sq Mt Per Ltr
- Polyester 3- 8* Sq Mt Per Ltr.
- Denim 3- 7* Sq Mt Per Ltr
- Leather 4- 10* Sq Mt Per Ltr

Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Application Method

Brush: Paint Brush with Soft bristle.
Garden Spray: Low Pressure High Volume.
Dipping: Material can be submerged in a pond of chemical.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in

Standard Testing Method

- Water Repellency: ASTM C67 or ASTM C140
- Stain Resistance: ASTM D1308
- Breathability: ASTM E96
- UV Resistance: ASTM G154
- Accelerated Weathering: ASTM G155

Pack Size

- 1 LTR
- 5 LTR
- 20 LTR
- 30 LTR
- 50 LTR

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Flammable.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in