WATER REPELLENT

Matt 200

Matt 200 is a Water Based Mild Wet Look Sealer for Unpolished Surfaces.

Technical Specification

Mixture of Organic Resin with Water.

Advantages

- Natural Matt Enhancement Without Artificial Gloss
- Mild Wet-Look Finish That Preserves Natural Appearance
- Deep Penetrating Protection for Porous Stone Surfaces
- Protects Against Water-Based Stains and Moisture
- Breathable Technology Allows Moisture Vapor to Escape
- No Surface Film Formation – Natural Stone Feel Retained
- UV Resistant for Long-Lasting Outdoor Performance
- Suitable for Both Interior and Exterior Applications
- Water-Based and Environmentally Friendly Formula
- VOC-Free and Low Odor
- Easy-to-use

Where to Use

- ✓ Marble
- ✓ Granite
- ✓ Sand Stone
- ✓ Concrete

Technical Data

- Appearance: liquid milky-white,
- Active ingredient: ca. 8 %
- Specific gravity at 20° C: ca. 1 g/cm³
- Application Temperature 15-30 °C
- Drying time 4 Hr.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- **Apply Sealer:** Spread two coats evenly till the surface is drenched for full coverage.
- **Penetration Time**: Allow 25–30 minutes to soak in.
- **Remove Excess:** Wipe off with clean, dry towels.
- **Curing:** Let it cure for 24-48 hours before use.

Typical Coverage

- Marble 10- 30* Sq Mt Per Ltr
- Granite 10- 30* Sq Mt Per Ltr
- Sand Stone 5- 10* Sq Mt Per Ltr.
- Concrete 5- 10* Sq Mt Per Ltr.

Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in

Application Method

Brush: Paint Brush with Soft bristle.
Fabric Roller: Short bristle.
Cotton Cloth: Clean White Cotton Cloth.
Garden Spray: Low Pressure High Volume.
Dipping: Material can be submerged in a pond of chemical.

Standard Testing Method

- Water Repellency: ASTM C67 or ASTM C140
- Stain Resistance: ASTM D1308
- Breathability: ASTM E96
- UV Resistance: ASTM G154
- Accelerated Weathering: ASTM G155

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.

Pack Size

- 1 LTR
- 5 LTR
- 20 LTR
- 30 LTR
- 50 LTR

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in