MatWet

MatWet is a Water Based Wet Look Sealer for Unpolished Surfaces.

Technical Specification

Mixture of Organic Resin with Water.

Advantages

- Rich Wet-Look Enhancement for Natural Surfaces
- Revives and Deepens Natural Color of Stone, Brick and Concrete
- Water-Based Technology for Safer Application
- Protects Against Water-Based Stains and Moisture Penetration
- Breathable Sealer Allows Moisture Vapor to Escape
- No Surface Film Formation – Maintains Natural Texture
- UV Resistant for Long-Term Outdoor Durability
- Suitable for Interior and Exterior Applications
- VOC-Free and Environmentally Friendly Formula
- Best for vertical application.
- Easy-to-use

Where to Use

- ✓ Sand Stone
- ✓ Concrete
- ✓ Brick
- ✓ Clay Tile

TECHNICAL DATA

- Appearance: liquid milky-white,
- Active ingredient: ca. 32 %
- Specific gravity at 20° C: ca. 1 g/cm³
- Application Temperature 15-30 °C
- Drying time 4 Hr.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- **Dilute:** MatWet with Mineral Water in Ratio 1:1 to 1:3
- **Apply Sealer:** Spread evenly for full coverage.
- **Penetration Time**: Allow 25–30 minutes to soak in.
- **Re-apply if Needed:** Repeat for porous surfaces.
- **Remove Excess:** Wipe off with clean, dry towels.
- **Curing:** Let it cure for 24-48 hours before use.

Typical Coverage

- Marble 10- 30* Sq Mt Per Ltr
- Granite 10- 30* Sq Mt Per Ltr
- Sand Stone 4- 10* Sq Mt Per Ltr
- Concrete 4- 10* Sq Mt Per Ltr

Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Application Method

Brush: Paint Brush with Soft bristle.
Fabric Roller: Short bristle.
Cotton Cloth: Clean With White Cotton Cloth.
Garden Spray: Low Pressure High Volume.

Trinity Rubber
"J" Type Shed , Plot No. 2314,Phase - III, G.I.D.C. Area,Vapi 396195
70963 34083
info@waterrepellent.in

Standard Testing Method

- **Water Repellency:** ASTM C67 or ASTM C140
- **Stain Resistance:** ASTM D1308
- **Breathability:** ASTM E96
- **UV Resistance:** ASTM G154
- **Accelerated Weathering:** ASTM G155

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use
- Non-Flammable.

Pack Size

- 1 LTR
- 5 LTR
- 20 LTR
- 30 LTR
- 50 LTR

Trinity Rubber
"J" Type Shed , Plot No. 2314,Phase - III, G.I.D.C. Area,Vapi 396195

70963 34083

info@waterrepellent.in