Stone Sealer 19

Stone Sealer 19 is a Solvent Based, Water & Oil Repellent Sealer for Polished Surface.

Technical Specification

Formulated with organic resin dispersed in hydrocarbon solvent.

Advantages

- Advanced Water & Oil Repellent Protection
- Invisible Protection with Natural Finish
- Protects Against Stains, Moisture & Weather Damage
- Breathable Formula – No Surface Film Formation
- Enhances Surface Life & Preserves Natural Beauty
- UV Resistant for Long-Lasting Exterior Performance
- Excellent Protection for Polished Stone Surfaces
- Suitable for Interior, Exterior & Countertop Applications
- Deep Penetrating Professional Grade Formula
- Easy Application with Fast Performance
- Low VOC & User-Friendly Technology

Where to Use

- ✓ Marble
- ✓ Granite
- ✓ Sand Stone
- ✓ Concrete

Technical Data

- Appearance: clear, liquid
- Odor less
- Specific gravity at 20°C: ca. 0.78 g/cm³
- Application Temperature 15-30 °C
- Drying time 4 Hr.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- **Apply Sealer:** Spread evenly for full coverage.
- **Penetration Time**: Allow 25–30 minutes to soak in.
- **Re-apply if Needed:** Repeat for porous surfaces.
- **Remove Excess:** Wipe off with clean, dry towels.
- **Curing:** Let it cure for 24-48 hours before use.

Typical Coverage

- Marble 10- 30* Sq Mt Per Ltr
- Granite 10- 30* Sq Mt Per Ltr
- Sand Stone 4- 10* Sq Mt Per Ltr
- Concrete 4- 10* Sq Mt Per Ltr

Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Trinity Rubber
"J" Type Shed , Plot No. 2314,Phase - III, G.I.D.C. Area,Vapi 396195

70963 34083

info@waterrepellent.in

Application Method

Brush: Paint Brush with Soft Bristle.
Fabric Roller: Short Bristle.
Cotton Cloth: Clean With White Cotton Cloth.
Garden Spray: Low Pressure High Volume.

Pack Size

- 1 LTR
- 5 LTR
- 20 LTR
- 30 LTR
- 50 LTR

Standard Testing Method

- Water Repellency: ASTM C67 or ASTM C140
- Stain Resistance: ASTM D1308
- Breathability: ASTM E96
- UV Resistance: ASTM G154
- Accelerated Weathering: ASTM G155

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Flammable.

Trinity Rubber
"J" Type Shed , Plot No. 2314,Phase - III, G.I.D.C. Area,Vapi 396195

70963 34083

info@waterrepellent.in