TPI CER

It is Anti-Scratch and Anti-Stain coating systems for Metal Surfaces.

Technical Specification

- Mixture of specialty Silicon Resin

Advantages

- Advanced Protection Against Oxidation & Corrosion
- Outstanding Weather & Environmental Resistance
- Superior Scratch & Abrasion Resistance
- High UV & Chemical Resistance for Long-Term Durability
- Excellent High-Temperature Stability
- Crystal Clear Transparent Protective Coating
- Super Hydrophobic Surface with Contact Angle >100°
- Permanent Gloss Retention & Enhanced Surface Appearance
- Creates a Self-Cleaning Water-Repellent Effect
- Preserves Original Metal Finish & Shine
- Reduces Maintenance & Surface Degradation
- Easy-to-use.

Where to Use

- ✓ All Metal Body (Steel, Copper, Gold, Silver, etc.)
- ✓ Faucet (Taps, Showers, etc.)

Technical Data

- Appearance: Clear, liquid
- Specific gravity at 20°C: ca. 0.68 g/cm³
- Application Temperature 15-30 °C
- Drying time 15 Min.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- Ensure the surface is dust free and Well-Polished.
- **Apply Sealer:** First coat spread evenly till the surface is fully covered.
- If required buff entire area with buffing Micro Fiber Buffing pad after 20 mins of application of 1st coat.
- **Curing:** Let it cure for 24-48 hours at room temperature before use.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in

Typical Coverage

- Depending on the metal surface.

  Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Application Method

Application Pad: Clean With White Cotton

Standard Testing Method

- Water Repellency: ASTM C67 or ASTM C140
- Stain Resistance: ASTM D1308
- UV Resistance: ASTM G154
- Accelerated Weathering: ASTM G155
- Scratch Test: ASTM D3363

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.

Pack Size

- 30 ML
- 50 ML

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in