TPI Glass Coat

IT is Stain resistance coating systems for Glass and Mirrors.

Technical Specification

Mixture of specialty Silicon Resin

Advantages

- Excellent adhesion for all Glass and Mirrors.
- Advanced Hydrophobic Technology (Water Contact Angle >110°)
- Crystal Clear Invisible Protection
- Outstanding Weather Resistance for Indoor & Outdoor Applications
- Superior Scratch Resistance for Lasting Clarity
- High UV Resistance Against Fading & Surface Aging
- Excellent High-Temperature Stability
- Permanent Gloss & Optical Clarity Retention
- Enhances Water Beading & Easy-Clean Performance
- Reduces Water Marks, Dust & Dirt Build-Up
- Transparent Coating with No Change in Visibility
- Professional Grade Nano Protection Technology
- Easy-to-use.

Where to Use

- ✓ Glass
- ✓ Mirrors
- ✓ Solar Panels

Technical Data

- Appearance: Clear, liquid
- Specific gravity at 20°C: ca. 0.68 g/cm³
- Application Temperature 15-30 °C
- Drying time 15 Min.
- Curing Time 24 Hr.

Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

How To Use

- Ensure the surface is dust free and Well-Polished.
- Clean Glass Using Klynn Surfa.
- Apply a uniform and rich coat of TPI Glass Coat on the clean and dust free surface with white cotton cloth.
- Buff after 10 mins of application.
- A full cure is achieved after 4-6 hours.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in

Typical Coverage

- Glass - 60-100 Sq Mt Per Ltr
- Mirrors - 60-100 Sq Mt Per Ltr
- Solar Panel- 60-100 Sq Mt Per Ltr

Note: Above mentioned coverage may differ depending on porosity, type of polish and application method.

Application Method

Application Pad: Clean With White Cotton.

Standard Testing Method

- Water Repellency: ASTM C67 or ASTM C140
- Stain Resistance: ASTM D1308
- UV Resistance: ASTM G154
- Accelerated Weathering: ASTM G155
- Scratch Test: ASTM D3363

Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.

Pack Size

- 1 LTR
- 5 LTR

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in