# TPI Stone Coat

**It is Anti-Scratch and Anti-Stain resistance coating systems for Stone Surfaces.**

## Technical Specification

Mixture of specialty Silicon Resin

## Advantages

- Excellent adhesion for all stone surfaces.
- Outstanding weather resistance.
- Good Scratch Resistance.
- Stops oxidation process.
- Suitable for vertical and horizontal surfaces.
- High UV and chemical resistance.
- Very high temperature stability.
- The coating is transparent.
- Contact angle (water) > 100°
- Permanent gloss retention.
- Good Chemical resistance property.
- Easy-to-use.

## Where to Use

✓ All Hard Mirror Polished Stone

## Technical Data

- Appearance: Clear, liquid
- Specific gravity at 20°C: ca. 0.68 g/cm³
- Application Temperature 15-30 °C
- Drying time 15 Min.
- Curing Time 24 Hr.

## Directions for Use

- Read the entire label and follow directions.
- Carry out a patch test on a small area first.
- Allow grout to cure for 72 hours before use.
- Ensure the surface is clean and dry.
- Apply within 20°C–30°C temperature range.
- Maintain proper ventilation during application.

## How To Use

- Ensure the surface is dust free and Well-Polished.
- **Apply Sealer:** First coat spread evenly till the surface is fully covered.
- If required buff entire area with buffing Micro Fiber buffing Pad after 20 mins of application of 1st coat.
- **Curing:** Let IT cure for 24-48 hours at room temperature before use.

## Typical Coverage

- Marble – 3-5 Sq Mtr Per 30 ML
- Granite- 3-5 Sq Mtr Per 30 ML

**Note**: Above mentioned coverage may differ depending on porosity, type of polish and application method.

## Application Method

**Application Pad:** Clean With White Cotton

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in

## Standard Testing Method

- Water Repellency: ASTM C67 or ASTM C140
- Stain Resistance: ASTM D1308
- UV Resistance: ASTM G154
- Accelerated Weathering: ASTM G155
- Scratch Test: ASTM D3363

## Pack Size

- 30 ML
- 50 ML

## Caution

- Keep out of reach of children.
- Do not disperse into the environment after use.

Trinity Rubber
Plot No. J - 2314, Phase - III, G.I.D.C. Area, Vapi 396195

70963 34083

info@waterrepellent.in